

M8195A 65 GSa/s Arbitrary Waveform Generator M8197A Multi-Channel Synchronization Module

Version 4.4

Introduction

The M8195A is the industry's most flexible arbitrary waveform generator offering a unique combination of high-channel density, high-sample rate, high-bandwidth, deep memory, and advanced functionalities such as sequencing with very precise triggering and external dynamic control. An embedded digital signal processor also enables real-time waveform and impairment generation.

Keysight's M8195A AWG accelerates your innovation giving you the versatility to create the signals needed for wideband wireless RF communications, digital applications, quantum communication and sensing, quantum computing, optical/electrical communications and general advanced research.



M8195A at a Glance

Go where you have never been able to test before: with real-time mode, sequencing and deep memory - explore your possibilities, and speed your test by up to 100 times with unique real-time mode.

- Sample rate up to 65 GSa/s
- 25 GHz analog bandwidth
- 8 bits vertical resolution
- Up to 1 Vpp(se), 2 Vpp(diff) output amplitude with voltage window between -1.0V and +3.3 V
- Up to 16 GSa of waveform memory per AXIe module
- Up to 4 differential channels per 1-slot high AXIe module (number of channels is software upgradeable)
- Up to 16 channels per 5-slot AXIe chassis¹
- Advanced 3-level sequencing with external dynamic control¹
- Load new waveforms on-the-fly without interrupting the playback of the previous one¹ ("memory ping-pong")
- Rise/fall time (20% / 80%) 18 ps (typ). With pre-distortion applied 12 ps (typ)
- Ultra-low intrinsic jitter (RJrms < 200 fs)
- Built-in frequency and phase response calibration for clean output signals
- Up to 64-tap FIR filter in hardware for frequency response compensation
- Up to 2 markers with 1 sample resolution (markers don't reduce vertical resolution)
- Embedded DSP enables real-time waveform and impairment generation

Key Applications

As devices and interfaces become faster and more complex, the M8195A AWG gives you the versatility to create the signals needed for wideband wireless RF communications, digital applications, quantum communication and sensing, quantum computing, optical/electrical communications and general advanced research.

- Wideband RF/ μ W – generate extreme wideband RF signals with an instantaneous bandwidth of DC to 25 GHz for aerospace/defense/communication applications.
- Multi-level / multi-channel digital signals – generate PRBS², NRZ, PAM4, PAM8, DMT, etc. signals of up to 32 Gbaud. Embed/de-embed channels, add jitter, ISI, noise and other distortions.
- Quantum applications – generate complex pulse shapes required for encoding and transmitting quantum information; generate microwave pulses that control the state of qubits in superconducting quantum computers; generate precise signals needed for various quantum sensing techniques.
- Coherent optical – a single M8195A module can generate two independent I/Q baseband signals (dual polarization = 4 channels) at up to 32 GBaud and beyond.
- Physics, chemistry and electronics research – generate any mathematically defined arbitrary waveforms, ultra-short yet precise pulses and extremely wideband chirps.

¹ Available with M8195A plus M8197A.

² PRBS pattern size includes PRBS7, PRBS10, PRBS11, PRBS15. For PRBS23, 31 will require extended 16 GSa/s memory option.

Wideband RF/ μ W signals

The M8195A can generate signals appropriate for wideband wireless 5G/6G application, radar, satellite and electronic warfare (EW) applications where extremely wide instantaneous bandwidth (DC to 25 GHz) and fast frequency hopping are critical parameters.

With built-in frequency and phase calibration, it is straight forward to generate wideband multi-tone signals with a flat frequency response up to 25 GHz.

Wideband wireless signals with any modulation scheme (e.g. nPSK, nQAM, APSK, OFDM, etc.) can be generated directly at carrier frequencies of up to 25 GHz. In many cases, this saves an additional up-conversion stage or enables waveform generation directly at the carrier frequency.

The M8195A addresses also the wide-bandwidth and performance demands for 6G research, e.g. sub-THz applications.




Figure 1. Multi-tone signal from 10 GHz to 15 GHz.

Quantum applications

The M8195A is a versatile AWG that plays a significant role in various quantum technologies, including quantum communication, quantum computing, and quantum sensing.

In quantum communication, the M8195A can generate complex pulse shapes required for encoding and transmitting quantum information, which is crucial for minimizing errors and maximizing the fidelity of quantum communication channels. In Quantum Key Distribution (QKD) systems, M8195A creates precise timing and amplitude of pulses needed for secure key exchange protocols. The M8195A can also help to generate specific waveforms required to create and manipulate entangled photon pairs, which is fundamental for quantum networks.

In Quantum Computing, the M8195A can generate microwave pulses that control the state of qubits in superconducting quantum computers. These pulses need to be extremely precise to ensure accurate qubit manipulation.

In Quantum Sensing, the M8195A can be used to control and measure quantum defects, such as nitrogen-vacancy centers in diamonds, or generate the precise signals needed for various quantum sensing techniques, including optically detected magnetic resonance (ODMR) and Rabi oscillations.

Multi-level/multi-channel digital signals

Increasing the data throughput on digital interfaces has traditionally been accomplished by increasing the data rate or by increasing the number of parallel signals. However, for certain applications, it is more cost-effective to consider multi-level signaling techniques.

Examples are high-speed backplane connections using PAM4 or PAM8, and also technologies in the mobile application space.

The M8195A is ideally suited to address those multi-level/multi-channel interfaces using any standard or custom data format, such as PAM-n ($n = 3, 4, 5, \dots$) or custom modulation formats. The M8195A supports pattern lengths up to PRBS $2^{31}-1$ ³ and baud rates exceeding 32 GBaud, including the necessary parameter changes, such as variable transition times, various pulse-shaping filters, adding distortions, and can also generate PAM-n signals with non-equidistant voltage levels. The flexibility of the waveform generation at highest speeds, combined with excellent intrinsic jitter performance makes the M8195A truly a future-proof instrument – independent of the direction technology is moving.




Figure 2. 4 PAM4 signal at 28 GBaud (= 56 Gbit/s).

At data rates of multiple Gb/s, the effect of cables, board traces, connectors etc. must be considered to generate the desired signal at the test point of the device under test. The M8195A incorporates digital pre-distortion techniques for frequency- and phase response compensation of the AWG output and any external circuit to generate the desired signal at the device under test. Channels can be embedded/de-embedded if the S-parameters of the respective circuits are provided.

³ PRBS waveforms are calculated and upload into AWG's waveform memory by software. For PRBS lengths up to $2^{15}-1$, the download time is negligible but for a PRBS $2^{31}-1$, this will take several minutes.




Figure 3. 32 Gb/s PRBS $2^{11}-1$ showing 138 fs RJrms.

With up to 4 differential output channels per 1-slot AXIe module and the ability to synchronize multiple modules, the M8195A is well-suited to stimulate multi-lane high-speed interfaces in a very economic fashion.

With the integration of the M8195A AWG into the M8000 Series of BER test solutions, Keysight allows you to address your high-speed digital receiver test needs with the M8070B software platform and choose the BERT or AWG that best meets your needs.

Coherent optical applications

The M8195A supports leading edge research for 100 Gb/s, 400 Gb/s and 1 Tb/s optical transmission systems that require a very wideband electrical stimulus with a variety of complex modulation formats from QPSK to nQAM to OFDM at symbol rates up to 32 GBaud and beyond.

In order to drive dual-polarization systems, the M8195A has 4 independent, yet precisely synchronized analog output channels in a single module. Since all 4 channels are generated by the same instrument without any external circuitry, precise synchronization down to the femto-second range can be achieved and maintained.




Figure 4. 16 QAM @ 32 GBaud.

The M8195A uses digital pre-distortion techniques for frequency- and phase- response compensation of the AWG output and any external circuits. These are required to achieve a clean signal at the device under test.

Distortions generated by cables, amplifiers, etc. can also be compensated by embedding /de-embedding the S-parameters of the respective circuits or by performing an in-situ calibration using Keysight 81195A Optical Modulation Generator software.

In conjunction with the 81195A Optical Modulation Generator software clean signals and signals stressed with impairment patterns can be generated both offline on a PC or in real-time using the hardware DSP block, which allows the parameters of the waveform (e.g., the pulse shaping filter coefficients) and impairment generation to be adjusted at run-time without downloading a new waveform.




Figure 5. Optical Modulation Generator Software.

Physics, chemistry and electronics research

You can generate any arbitrary waveform that you can mathematically describe (e.g. in MATLAB or Python) and download it directly to the M8195A. This includes ultra-short yet precise pulses down to ~100 ps pulse width or extremely short, yet wideband RF pulses and chirps.

In conjunction with the M8197A synchronization module, these signals can be triggered from external sources with very low jitter.



Figure 6. 100 ps pulse with 17 ps risetime.



Figure 7. Four different pulsed signals up to 25 GHz.

M8197A

The M8197A is a synchronization module for up to four M8195A modules. Using the M8197A, a fully synchronous system with up to 16 channels per AXIe 5-slot chassis can be realized. The M8197A also provides a dynamic control input/general purpose output that can be used with one or more M8195A modules. Trigger-to-output delay accuracy is improved when using the M8197A trigger input (see timing characteristics paragraph).



Figure 8. M8197A, front panel view and system with 16 synchronized channels (4x M8195A modules and 1x M8197A module).

Software

The basic functionality of the M8195A is controlled from a soft front panel application running on the AXIe embedded controller or external PC or laptop. In addition to basic settings such as sample clock rate, output amplitudes, etc., the soft front panel offers functionality to:

- Load waveforms from files
- Generate standard waveforms (sine, square, etc.)
- Generate multi-tone waveforms
- Generate complex modulated waveforms (nPSK, nQAM, etc.)
- Generate binary and multi-level digital waveforms
- Generate serial data waveforms
- Control FIR filters

In addition to the soft front panel, the M8195A can be controlled via SCPI and IVI-COM remote programming interfaces.

External software applications that can be used to generate and download waveforms directly to the M8195A via SCPI or IVI-COM include MATLAB, Python, LabView, C++, C# or any other .NET language.

The M8195A is integrated into the following Keysight software applications:

- M8070B - system software for M8000 Series of BER test solutions
- N5991x (HDMI, USB) - Test Automation Software
- M8085A - MIPI® receiver test solutions
- 81195A - optical modulation generator software
- W48xB – PathWave System Design (SystemVue) electronic system-level design software
- N7618APPC PathWave Signal Generation (PWSG) Advanced Waveform Utility (AWU)

For additional information see the respective data sheets.

Configuration

The following products/options are available.

Product numbers	Description	Comments
M8195A-001	1 channel, 65 GSa/s, 2 GSa per module	Including local start-up assistance and one 50 Ω termination for each channel
M8195A-002	2 channel, 65 GSa/s, 2 GSa per module	
M8195A-004	4 channel, 65 GSa/s, 2 GSa per module	
M8195A-16G	Upgrade to 16 GSa per module	Software license
M8195A-SEQ	Sequencer functionality per module	Software license
M8195A-FSW	Fast switching per module	Software license
M8195A-1A7	ISO 17025 report	
M8195A-Z54	Z54 calibration report	
M8195A-BU1	Pre-configured system including one M9505A 5-slot AXIe Chassis with USB Option and one M9537A AXIe Embedded PC Controller	
M8195A-BU2	Pre-configured system including one M9502A 2-slot AXIe Chassis with USB Option	
M8195A-BU3	Pre-configured system including one M9502A 2-slot AXIe Chassis with USB Option and one M9537A AXIe Embedded PC Controller	
M8197A	Synchronization module for up to four M8195A modules	Including four synchronization cables
M8195S	Pre-configured Arbitrary Waveform Generator System including one M8197A	In addition to the required modules, a local start-up assistance, one 50 Ω termination for each channel and an AXIe chassis with an embedded controller or external PC connectivity will automatically be added.

Upgrades options for M8195A

Product numbers	Description	Comments
M8195AU-U02	Upgrade from 1 ch. to 2 ch.	Software license
M8195AU-U04	Upgrade from 2 ch. to 4 ch.4	Software license
M8195AU-16G	Upgrade to 16 Gsa per module	Software license
M8195AU-SEQ	Sequencer functionality per module	Software license
M8195AU-FSW	Fast switching per module	Software license

⁴ For an upgrade from 1 to 4 channels, both M8195AU-002 and M8195AU-U04 are required.

Accessories

To be operational, an AXI chassis plus either an embedded controller or external PC or laptop are required in addition to one or more M8195A/M8197A modules. (See <http://www.keysight.com/find/AXIe> for more details.)

Product numbers	Description	Comments
M9502A-U20	2 slot AXIe chassis with USB option	
M9505A-U20	5 slot AXIe chassis with USB option	
M9537A	AXIe embedded controller	
8121-1243	Cable-Assembly USB Type A-MINI B 28-AWG 5-Conductor 2-M-LG PVC	
M9048B	PCIe® Host Adapter: Single Port (x8), Gen3	
Y1202A	PCIe cable for M9048B desktop adapter	
M8195A-810	Matched cable pair for M8195A AWG, 2.92 mm	
M8195A-820	Termination 50 Ω , 26.5 GHz	

Software

Product numbers	Description	Comments
81195A	Optical Modulation Generator Software	Free to download
81195A-RSP	Real-Time Signal Processing	Requires 81195A
81195A-OSP	Optical Signal Properties	
M8070A-OTP	System Software for M8000 Series of BER Test Solutions, Transportable, Perpetual License	
M8070A-ONP	System Software for M8000 Series of BER Test Solutions, Network/Floating, Perpetual License	
M8070A-1TP	DUT Control Interface, Transportable, Perpetual License	
M8085A-CT1	MIPI C-PHYsm Editor for M819xA AWG, transportable, perpetual License	Requires M8070A license
M8085A-CN1	MIPI C-PHY Editor for M819xA AWG, network/floating, perpetual License	
M8085A-CTA	MIPI C-PHY Calibration, Conformance and Characterization Procedures for M819xA AWG, Transportable, Perpetual License	
M8085A-CNA	MIPI C-PHY Calibration, Conformance and Characterization Procedures for M819xA AWG, Network/Floating, Perpetual License	
M8085A-DT1	MIPI D-PHY sm Editor for M819xA AWG, transportable, perpetual License	
M8085A-DN1	MIPI D-PHY Editor for M819xA AWG, network/floating, perpetual License	
M8085A-DTA	MIPI D-PHY Calibration, Conformance and Characterization Procedures for M819xA AWG, transportable, perpetual License	
M8085A-DNA	MIPI D-PHY Calibration, Conformance and Characterization Procedures for M819xA AWG, Network/Floating, Perpetual License	
N6171A-M02	MATLAB license (standard)	
N6171A-M03	MATLAB license (extended)	

Specifications

General characteristics

M8195A	
Sample rate	53.76 GSa/s to 65.00 GSa/s or 26.88 GSa/s to 32.50 GSa/s (sample rate divider = 2) or 13.44 GSa/s to 16.25 GSa/s (sample rate divider = 4)
DAC resolution	8 bits
Number of channels per M8195A module	1, 2 or 4 (corresponds to option 001, 002, 004) (number of channels is software upgradable via license key)

Useable number of Channels with extended memory

Option			Mode	Sample rate divider		
001	002	004		1	2	4
001	002	004		53.76 GSa/s to 65.00 GSa/s	26.88 GSa/s to 32.50 GSa/s	13.44 GSa/s to 16.25 GSa/s
				max. 16G memory	max. 8G memory	max. 4G memory
			Single channel ⁵	1	1	1
			Single channel with marker	1	1	1
			Single channel duplicate	1	1	N/A
			Dual channel ⁵	1	2	2
			Dual channel with marker ⁵	1	2	2
			Dual channel duplicate	N/A	2	N/A
			Four channels ⁵	1	2	4

Channel duplicate mode

In “Single channel duplicate mode” the signal on channel 1 is duplicated on channel 3, channel 2 and channel 4 are unused. In “Dual channel duplicate mode” the signal on channel 1 is duplicated on channel 3 and the signal on channel 2 is duplicated on channel 4.

This mode allows differential signals to be generated with adjustable skew between normal and complement.

Run modes

M8195A and M8197A

Continuous	
Int. Memory	A waveform segment is continuously repeated
Ext. Memory	A waveform segment/sequence/scenario is continuously repeated
Triggered	
Int. Memory	A waveform segment is looped continuously after a trigger event is received
Ext. Memory	A waveform segment/sequence/scenario is generated once after a trigger event is received
Gated	
Int. Memory	A waveform segment is looped continuously after a rising edge of the trigger/gate input
Ext. Memory	A waveform segment/sequence/scenario is generated if the trigger/gate input is high

Sample Memory

M8195A

Internal sample memory	1 MSa per module (for modes of operation see Sample memory modes table below)
Extended sample memory	2 GSa per M8195A module (standard)16 GSa per M8195A module (with option 16G) (for modes of operation see Sample memory modes table below)
Waveform granularity ⁵	
Int. memory	128 samples
Ext. memory, sample rate divider = 1	256 samples
Ext. memory, sample rate divider = 2	128 samples
Ext. memory, sample rate divider = 4	64 samples
Minimum waveform length	
Int. memory	128 samples
Ext. memory, sample rate divider = 1	1280 samples
Ext. memory, sample rate divider = 2	640 samples
Ext. memory, sample rate divider = 4	320 samples

⁵ The length of waveform segments must be a multiple of the granularity.

Sample memory modes

Mode	Available with option	Sample memory (standard)	Sample memory (with opt. 16G)	Max. sample rate	Interpolation ⁶	Max. output frequency ⁷	Analog BW (typ) (3 dB)
1 ch, ext. mem.	001, 002, 004	2 GSa	16 GSa	65 GSa/s	None	> 25 GHz	25 GHz
1 ch, int. mem.	001, 002, 004	1 MSa	1 MSa	65 GSa/s	None	> 25 GHz	25 GHz
2 ch, ext. mem.	002, 004	1 GSa per ch.	8 GSa per ch.	32.5 GSa/s	2 x	12.8 GHz	25 GHz
2 ch, int. mem.	002, 004	512 KSa per ch.	512 KSa per ch.	65 GSa/s	None	> 25 GHz	25 GHz
4 ch, ext. mem.	004	0.5 GSa per ch.	4 GSa per ch.	16.25 GSa/s	4 x	6.4 GHz	25 GHz
4 ch, int. mem.	004	256 KSa per ch.	256 KSa per ch.	65 GSa/s	None	> 25 GHz	25 GHz

Markers

Two independent digital markers and their complements are available in single channel with markers and dual channel with markers mode. The markers are available only for channels on extended memory. They are provided on channel 3 and 4 on normal and complement.

In all other modes, no markers are available. Markers do not reduce vertical resolution.

The granularity of markers is one sample, a maximum of one rising and one falling edge of a marker are possible within 128 samples.

⁶ Interpolation is performed by FIR filters in hardware. For 2x (4x) interpolation, samples are read from memory at a rate up to 32.5 GSa/s (16.25 GSa/s) and interpolated to a DAC sample rate of up to 65 GSa/s. For interpolation = none, the sample rate from memory is the same as the DAC sample rate.

⁷ With default FIR configuration the maximum sample rate is calculated as 80% of Nyquist. With custom FIR configurations higher output frequencies can be achieved.

Out 1, 2, 3, 4

M8195A

Output type	Single ended ⁸ or differential
Bandwidth (3 dB, with sin(x)/x roll-off mathematically compensated)	25 GHz (typ)
Rise/fall time ⁹ (20% / 80%)	18 ps (typ)
Impedance	50 Ω (nom)
Output amplitude	75 mVpp to 1.0 Vpp, single-ended into 50 Ω 150 mVpp to 2.0 Vpp, differential
Amplitude resolution	200 μ V (nom)
DC amplitude accuracy ¹⁰	$\pm$ (2.5% +10 mV) (typ)
Voltage window	-1.0 V to +3.7 V single-ended into 50 Ω
Offset resolution	200 μ V (nom)
DC offset accuracy ¹¹	$\pm$ 20 mV (typ)
Differential offset	In system adjustable to 0 mV
Termination voltage window	-1.0 V to + 3.7 V $V_{OL} \leq 1.5$ V: (low level - 500 mV) to (high level +1000 mV) $V_{OL} > 1.5$ V: low level to (high level +1000 mV)
Total jitter, with pre-distortion	6 ps (pp) at 32 Gb/s PRBS (nom)
Random jitter, RMS ¹²	200 fs (typ)
Harmonic distortions ^{13 14}	
– 2nd harmonic	-45 dBc (typ), $f_{OUT} < 3$ GHz -35 dBc (typ), $f_{OUT} = 3$ GHz... 6 GHz -30 dBc (typ), $f_{OUT} > 6$ GHz
– 3rd harmonic	-45 dBc (typ), $f_{OUT} < 1$ GHz -40 dBc (typ), $f_{OUT} = 1$ GHz... 3 GHz -35 dBc (typ), $f_{OUT} = 3$ GHz... 6 GHz -30 dBc (typ), $f_{OUT} > 6$ GHz
Two-tone IMD ¹³	-45 dBc (typ), $f_{OUT1} = 990$ MHz, $f_{OUT2} = 1010$ MHz
SFDR ¹³ (excluding harmonic distortions)	

⁸ Unused output must be terminated with 50 Ω to GND. In case the termination voltage is not GND, the unused output must be terminated to VTerm.

⁹ Sample rate 64 GSa/s, output amplitude 500 mVpp(se).

¹⁰ Termination voltage = 0 V; adjusted at 23 °C ambient temperature, amplitude increases by 0.2%/°C (typ) for ambient temperature below 23 °C.

¹¹ Termination voltage = 0 V.

¹² 10 GHz clock; 1 V ampl.; 60 GSa/s.

¹³ Sample rate 64 GSa/s, output amplitude 500 mVpp(se).

¹⁴ Measured with a balun (e.g. HL 9405).

M8195A

– In-band	-80 dBc (typ), $f_{OUT} = 100$ MHz, measured DC to 1 GHz
	-70 dBc (typ), $f_{OUT} = DC...400$ MHz, measured DC to 400 MHz
	-48 dBc (typ), $f_{OUT} = DC...4$ GHz, measured DC to 4 GHz
	-53 dBc (typ), $f_{OUT} = 4$ GHz...6 GHz, measured 4 GHz to 6 GHz
	-53 dBc (typ), $f_{OUT} = 6$ GHz...8 GHz, measured 6 GHz to 8 GHz
	-50 dBc (typ), $f_{OUT} = 8$ GHz...10 GHz, measured 8 GHz to 10 GHz
	-46 dBc (typ), $f_{OUT} = 10$ GHz...12 GHz, measured 10 GHz to 12 GHz
	-50 dBc (typ), $f_{OUT} = 12$ GHz...14 GHz, measured 12 GHz to 14 GHz
	-42 dBc (typ), $f_{OUT} = 14$ GHz...16 GHz, measured 14 GHz to 16 GHz
	-42 dBc (typ), $f_{OUT} = 16$ GHz...18 GHz, measured 16 GHz to 18 GHz
	-42 dBc (typ), $f_{OUT} = 18$ GHz...20 GHz, measured 18 GHz to 20 GHz
	-48 dBc (typ), $f_{OUT} = 20$ GHz...21 GHz, measured 20 GHz to 21 GHz
	-42 dBc (typ), $f_{OUT} = 21$ GHz...22 GHz, measured 21 GHz to 22 GHz
	-40 dBc (typ), $f_{OUT} = 22$ GHz 24 GHz, measured 22 GHz to 24 GHz
	-40 dBc (typ), $f_{OUT} = 24$ GHz 26 GHz, measured 24 GHz to 26 GHz
– Adjacent band	-48 dBc (typ), $f_{OUT} = DC...4$ GHz, measured DC to 8 GHz
	-48 dBc (typ), $f_{OUT} = 4$ GHz...6 GHz, measured 3 GHz to 8 GHz
	-34 dBc (typ), $f_{OUT} = 6$ GHz...8 GHz, measured 4 GHz to 10 GHz
	-34 dBc (typ), $f_{OUT} = 8$ GHz...10 GHz, measured 6 GHz to 12 GHz
	-46 dBc (typ), $f_{OUT} = 10$ GHz...12 GHz, measured 8 GHz to 14 GHz
	-42 dBc (typ), $f_{OUT} = 12$ GHz...14 GHz, measured 10 GHz to 16 GHz
	-32 dBc (typ), $f_{OUT} = 14$ GHz...16 GHz, measured 12 GHz to 18 GHz
	-30 dBc (typ), $f_{OUT} = 16$ GHz...18 GHz, measured 14 GHz to 20 GHz
	-40 dBc (typ), $f_{OUT} = 18$ GHz...20 GHz, measured 16 GHz to 22 GHz
	-35 dBc (typ), $f_{OUT} = 20$ GHz 22 GHz, measured 18 GHz to 24 GHz
Amplitude flatness (at SMA connector, ¹⁵ with $\sin(x)/x$ roll-off mathematically compensated)	± 2 dB (typ), $f_{OUT} = DC...10$ GHz
	+2 dB, -3 dB (typ), $f_{OUT} = 10...25$ GHz (typ)
Connector type	2.92 mm “K-style” (female)

¹⁵ Measured at Data Out.

Phase Noise




Figure 9. Nominal phase noise measured with a sample rate of 64 GSa/s, at Out 1, single ended, 500 mV amplitude

Frequency response




Figure 10. Nominal frequency response measured with a sample rate of 64 GSa/s and a multi-tone signal containing frequencies from DC to 32 GHz with equal amplitudes.

ENOB

ENOB measured at 64 GSa/s using the sine fit method according to IEEE Std 1658-2011 with a sampling scope. Bandwidth is limited to maximum tone frequency, except for the ones labeled with Nyquist.




Figure 11. Nominal ENOB measured on a differential signal combined by a 50 GHz Balun Hyperlabs HL9405 with a sample rate of 64 GSa/s, internal clock and 500 mV amplitude at different bandwidths.

Frequency switching characteristics

M8195A	
Effective frequency switching time ¹⁶	
with option FSW	38 ps
without option FSW	> 505 μs

¹⁶ Effective switching frequency is determined as $1/f_{\max}$, with $f_{\max} = f_{\text{Sa(max)}} / 2.5$

Sequencer modes

The sample memory can be split into about of 13 M (13 421 772) waveform segments.

Waveform segments can have different sizes, but the segment size must be the same across channels.

The sequence table can contain up to 13 M entries (sequence IDs).

M8195A

Arbitrary	
Int. Memory	One waveform segment of arbitrary length is continuously looped
Ext. Memory	
Sequence (requires opt. SEQ)	
Int. Memory	Not available
Ext. Memory	One or more waveform segments are arranged in a linear sequence. Each segment can be repeated a programmable number of times or until an external event is signaled.
Scenario (requires Opt. SEQ)	
Int. Memory	Not available
Ext. Memory	One or more sequences are arranged in a linear sequence. Each sequence can be repeated a programmable number of times or until an external event is signaled

Trigger/gate input

A trigger/gate input is provided on the front panel of the M8195A and the M8197A. The trigger input is used to start/gate waveform playback.

- The trigger/gate input of the M8195A affects the channels of that M8195A.
- The trigger/gate input of the M8197A affects all channels of all M8195A that are combined in a multi-module system. To achieve best delay accuracy between trigger/gate input and the OUT signals, use the trigger/gate input of the M8197A. See timing characteristics below.

M8195A and M8197A	
Input range	-4 V to +4 V
Threshold	
Range	-4 V to +4 V
Resolution	10 mV (nom)
Sensitivity	100 mV (typ)
Polarity	Selectable, positive or negative
Input impedance	50 Ω (nom), DC coupled
Max. toggle rate¹⁷	
Sample rate divider = 1	Sample rate/3584
Sample rate divider = 2	Sample rate/1792
Sample rate divider = 4	Sample rate/896
Connector type	SMA (female)

¹⁷ Without option -FSW the trigger interval is limited as described under the 'Frequency switching characteristics'.

Event input

An event input is provided on the front panel of the M8195A and the M8197A. It is used in conjunction with the sequencer to advance to the next waveform segment or sequence.

- The event input of the M8195A affects the channels of that M8195A.
- The event input of the M8197A affects all channels of all M8195A that are combined in a multi-module system.

M8195A and M8197A	
Input range	-4 V to +4 V
Threshold	
Range	-4 V to +4 V
Resolution	10 mV (nom)
Sensitivity	100 mV (typ)
Polarity	Selectable, positive or negative
Input impedance	50 Ω (nom), DC coupled
Connector type	SMA (female)

Trigger output (M8195A only)

The “Trigger output” and “Event input” functions share the same connector on the front panel.

The “Trigger output” functionality is only used in conjunction with the 81195A Optical Modulation Generator Software. For details of using the “Trigger output” functionality, refer to the 81195A data sheet and user guide.

M8195A	
Output impedance	50 Ω (nom)
Level	
Voltage window	-0.5 V to 2.0 V
Amplitude	200 mVpp to 2.5 Vpp
Resolution	10 mV
Accuracy	$\pm (10\% + 25 \text{ mV})$ (typ)
Rise/fall time (20% to 80%)	150 ps (nom)
Width	20 ns (1280 sample clock cycles @ 64 GS/s)

Dynamic control input/general purpose output (M8197A only)

A bidirectional parallel input and output port is provided on the front panel of the M8197A synchronization module. When the port is configured as input, it can be used as 'dynamic control input' for all channels of a synchronous system to control the sequencing by external hardware. The dynamic control input affects all channels of a synchronous system. When the port is configured as a parallel output, the 14 digital lines can be individually controlled by software to represent logical states zero or one.

A detailed description of the dynamic control input, including timing diagram and pin assignment, is shown in the M8195A User's Guide

M8197A	
Configuration as input	
Input signals	Data[0..12]_In, Data_Select, Load
Number of addressable segments	$2^{24} = 16\,777\,216$
Data rate	DC to 1 MHz
Setup time	3.0 ns ('Data[0..12]_In', 'Data_Select' to rising edge of 'Load')
Hold time	0.0 ns (rising edge of 'Load' to 'Data[0..12]_In', 'Data_Select')
Input range	
Low level	0 V to +0.7 V
High level	+1.6 V to 3.6 V
Input impedance	Internal 10 k Ω (nom) to GND
Configuration as output	
Output signals	Data[0..13]_Out
Output range	
Low level (-12 mA to 0 mA)	0 V to +0.4 V
High level (0 mA to 12 mA)	+2.4 V to 3.3 V
Connector type	20 pin mini D ribbon (MDR) connector ¹⁸

¹⁸ Manufacturer: 3M. Manufacturer Part Number: N10220-52B2PC.

Timing characteristics

The sequencing of a single M8195A can be controlled with the 'Trigger/Gate Input' as well as the 'Event Input' of the M8195A. In a synchronous system that consists of one M8197A and up to four M8195A, the sequencing of the entire synchronous system can be controlled with the 'Trigger/Gate Input' as well as the 'Event Input' of the M8197A. A single M8195A or a synchronous system can operate asynchronously or synchronously. In case of synchronous operation, a timing requirement between the Reference Clock Output and 'Trigger/Gate Input' or 'Event Input' must be met.

	M8195A	M8197A
Delay		
Trigger/Gate Input to Data Out	40192 sample clock cycles + 0 ns (nom) ¹⁹	45317 sample clock cycles + 8 ns (nom)
Event Input to Data Out	40192 sample clock cycles + 0.15 ns (nom) ¹⁹	45317 sample clock cycles + 8 ns (nom)
Delay accuracy, asynchronous operation		
Trigger/Gate Input to Data Out	± 100 ps (typ) ¹⁹	± 20 ps (typ)
Event Input to Data Out	± 100 ps (typ) ¹⁹	± 100 ps (typ)
Synchronous operation		
Delay accuracy	1ps _{rms} (typ) (Rising edge of 'REF CLK OUT' to 'DATA OUT') ¹⁹	1ps _{rms} (typ) (Rising edge of 'REF CLK OUT' to 'DATA OUT')
Set-up time	-2.5 ns (typ) ('TRIG IN', 'EVENT IN' to rising edge of 'REF CLK OUT') ¹⁹	-1.9 ns (typ) ('TRIG IN', 'EVENT IN' to rising edge of 'REF CLK OUT')
Hold time	5.1 ns (typ) (Rising edge of 'REF CLK OUT' to 'TRIG IN', 'EVENT IN') ¹⁹	4.5 ns (typ) (Rising edge of 'REF CLK OUT' to 'TRIG IN', 'EVENT IN')
Skew between normal and complement	0 ps ± 1 ps (nom)	
Skew between any pair of outputs		
Within one M8195A module	0 ps ± 5 ps (typ) ²⁰	
Across multiple M8195A modules	0 ps ± 100 ps (typ) ²¹	

¹⁹ Delay and delay accuracy specifications are valid for all modes except for the external reference clock setting 1.68 to 2.03125 GHz. For this setting the delay is non-deterministic.

²⁰ Can be adjusted to 0 ps using variable channel delay

²¹ Can be adjusted to 0 ps using variable module delay and variable channel delay.

Variable channel delay

To compensate for external cable length differences as well as the initial skew, channels 1, 2, 3 and 4 can be individually delayed with a very high timing resolution. There are two possibilities to adjust the variable channel delay.

- The sample clock delay can be changed in discrete steps. The step size is 1 / DAC Sample Frequency. E.g. the step size is 15.625 ps for a DAC Sample Frequency of 64 GHz.
- The FIR delay can be used for sub sample delay adjust. Note: This delay functionality uses a digitally implemented FIR filter with limited length and accuracy. As a result, the output signal may show some degradation when using the FIR delay adjust.

M8195A	
Sample clock delay range	0 ... 95 sample clocks
FIR delay range	
Sample Rate Divider = 1	-50 ps...+50 ps
Sample Rate Divider = 2	-100 ps...+100 ps
Sample Rate Divider = 4	-200 ps...+200 ps
FIR delay resolution	10 fs
Sample clock delay range	0 ... 95 sample clocks

Variable module delay

To compensate for external cable length differences as well as the initial skew, channels 1, 2, 3 and 4 can be jointly delayed with a very high timing resolution. In case the M8197A synchronization module is used to configure a synchronous system, the variable delay can be used to align the channels of multiple M8195A modules.

Modifying the variable delay always affects the delay of all four channels.

E.g. setting the variable delay to 10 ps has the following effect. Out 1, 2, 3 and 4 are delayed by 10 ps with respect to trigger/gate input and event input.

M8195A	
Delay range	0 ns to 10 ns ²²
Delay resolution	50 fs
Delay accuracy	± 10 ps (typ)

²² When using the external reference clock setting 1.68 to 2.03125 GHz, the variable module delay is not available.

FIR Filter

Each channel in the M8195A has an FIR filter with programmable coefficients in front of its respective DAC. The FIR filters are used to realize variable channel delay and waveform interpolation with sample rate divider 2 and 4. The following presets are available for the FIR filter coefficients: Nyquist, Low Pass, Linear Interpolation, Zero Order Hold and User Defined. The number of taps of each filter is 16 when internal memory is used and depends on the sample rate divider when extended memory is used as shown in the following table.

Sample rate divider	Taps	Memory sample rate	DAC sample rate
1	16	53.76 GSa/s ... 65.00 GSa/s	53.76 GSa/s ... 65.00 GSa/s
2	32	26.88 GSa/s ... 32.50 GSa/s	53.76 GSa/s ... 65.00 GSa/s
3	64	13.44 GSa/s ... 16.25 GSa/s	53.76 GSa/s ... 65.00 GSa/s

Reference clock input

The clock reference input is provided on the front panel of each module. The clock reference input of the M8195A is used as the clock reference for all four channels of that M8195A. The clock reference input of the M8197A synchronization module is used as the clock reference for all channels of all M8195A that are combined in a synchronous system.

M8195A and M8197A	
Input frequency ranges	10 MHz to 300 MHz
	210 MHz to 17 GHz
	1.68 GHz to 2.03125 GHz (M8195A only, DAC sample rate is fixed at 32x input frequency)
Lock range	± 1% (typ)
Jitter	< 2 pS _{pp}
Input level	
10 MHz - 10 GHz	250 mV _{pp} to 2 V _{pp}
10 GHz - 17 GHz	500 mV _{pp} to 2 V _{pp}
Impedance	50 Ω (nom), AC coupled
Connector	SMA
Sample clock frequency resolution	1 ppm; e.g. sample clock frequency = 64 GHz => frequency resolution = 64 kHz

Reference clock output

The clock reference input is provided on the front panel of each module. The clock reference input of the M8195A is used as the clock reference for all four channels of that M8195A. The clock reference input of the M8197A synchronization module is used as the clock reference for all channels of all M8195A that are combined in a synchronous system.

M8195A and M8197A	
AXIe backplane clock source	
Output frequency	$f_{OUT}^{23} = f_{Sa} / (32 * n)$ with $n = 1 \dots 1024$ or $f_{OUT}^{24} = f_{Sa} / 256$
Frequency accuracy	± 20 ppm
Internal clock source	
Output frequency	$f_{OUT}^{23} = f_{Sa} / (32 * n)$ with $n = 1 \dots 1024$ or $f_{OUT}^{24} = f_{Sa} / 256$ or $f_{OUT}^{24} = 100$ MHz
Frequency accuracy	See internal synthesizer clock characteristic
External reference clock: input frequency $f_{IN} = 10$ MHz to 300 MHz	
Output frequency	$f_{OUT}^{24} = f_{IN} / (n * m)$ with $n, m = 1 \dots 8$ or $f_{OUT}^{24} = f_{Sa} / 256$
Frequency accuracy	Depends on external reference clock
External reference clock: input frequency $f_{IN} = 210$ MHz to 17 GHz	
Output frequency	$f_{OUT}^{23} = f_{Sa} / (32 * n)$ with $n = 1 \dots 1024$ or $f_{OUT}^{24} = f_{Sa} / 256$
Frequency accuracy	Depends on external reference clock
External reference clock: input frequency $f_{IN} = 1.68$ GHz to 2.03125 GHz (M8195A only, DAC runs at fixed rate $f_{Sa} = 32 * f_{IN}$)	
Output frequency	$f_{OUT} = f_{IN} / 8 = f_{Sa} / 256$
Frequency accuracy	Depends on external reference clock
Output amplitude	900 mV _{pp} (nom) into 50 Ω
Source impedance	50 Ω (nom), AC coupled
Connector	SMA

²³ Reference clock output phase shifts when the variable delay is changed.

²⁴ For M8195A: Reference clock output remains unchanged when the variable delay is changed.

Internal synthesizer clock characteristics

M8195A	
Frequency	53.76 GHz to 65.00 GHz
Accuracy ²⁵	± 2 ppm (spec)
Frequency resolution	7 digits, e.g. 100 Hz at 1 GHz
Phase noise ²⁶	< -115 dBc/Hz (typ) at 10 kHz offset, $f_{OUT} = 1$ GHz
	< -95 dBc/Hz (typ) at 10 kHz offset, $f_{OUT} = 10$ GHz

Download speed

Download speed is measured by transferring the samples from the controlling PC's memory into the M8195A.

	USB using SCPI or IVI	PCIe using SCPI ²⁷	PCIe using IVI ^{27 28}
Download Speed	~8 MSa/s (meas)	~40 MSa/s (meas)	~400 MSa/s (meas)

Instrument software

The M8195A and M8197A are controlled by a combined soft-front panel and firmware application that runs on an embedded AXIe controller or external PC or laptop.

M8195A and M8197A	
Supported Operating Systems	Windows 10 (32 or 64 bit), Windows 11
Required hard disk space	1 GB
Interface to hardware	PCI Express [®] or USB
Application programming interfaces	SCPI, IVI-COM, LabView

²⁵ Warm-up time 2 minutes min.

²⁶ $f_{Sa} = 64$ GHz; reference clock source: internal.

²⁷ Using M9048A PCIe adapter.

²⁸ Download of waveform samples without marker information

General

	M8195A	M8197A
Power consumption	180 W (nom) @ 65 GSa/s	60 W (nom)
Operating temperature		0 °C to 40 °C
Operating humidity	5% to 80% relative humidity, non-condensing	
Operating altitude		Up to 2000 m
Storage temperature		-40 °C to +70 °C
Stored states	User configurations and factory default	
Interface to controlling PC	PCIe (see AXIe chassis specification) or USB	
Form factor		1-slot AXIe
Dimensions (W x H x D)		322.25 mm x 30 mm x 281.5 mm
Weight	3.75 kg	2.7 kg
Safety designed to	IEC61010-1, UL61010, CSA22.2 61010.1 tested	
EMC tested to		IEC61326-1
Warm-up time		30 min
Calibration interval		2 years recommended
Cooling requirements	When operating the system choose a location that provides at least 80 mm of clearance at rear, and at least 30 mm of clearance at each side	

Definitions

Specification (spec)

The warranted performance of a calibrated instrument that has been stored for a minimum of 2 hours within the operating temperature range of 0 °C to – 40 °C and after a 45-minute warm-up period.

Within ± 10 °C after auto cal. All specifications include measurement uncertainty and were created in compliance with ISO-17025 methods. Data published in this document are specifications (spec) only where specifically indicated.

Typical (typ)

The characteristic performance, which 80% or more of manufactured instruments will meet. This data is not warranted, does not include measurement uncertainty, and is valid only at room temperature (approximately 23 °C).

Nominal (nom)

The mean or average characteristic performance, or the value of an attribute that is determined by design such as a connector type, physical dimension, or operating speed. This data is not warranted and is measured at room temperature (approximately 23 °C).

Measured (meas)

An attribute measured during development for purposes of communicating the expected performance. This data is not warranted and is measured at room temperature (approximately 23 °C).

Accuracy

Represents the traceable accuracy of a specific parameter. Includes measurement error, time base error, and calibration source uncertainty.

Confidently Covered by Keysight Services

Prevent delays caused by technical questions, or system downtime due to instrument maintenance and repairs with Keysight Services. Keysight Services are here to support your test needs with expert technical support, instrument repair and calibration, software support, training, alternative acquisition program options, and more.

A KeysightCare agreement provides dedicated, proactive support through a single point of contact for instruments, software, and solutions. KeysightCare covers an extensive group of instruments, application software, and solutions and ensures optimal uptime, faster response, faster access to experts, and faster resolution.

Keysight services

Offering	Benefits
KeysightCare 	KeysightCare provides elevated support for Keysight instruments and software, with access to technical support experts that respond within a specified time and ensure committed repair and calibration turnaround times (TAT). KeysightCare offers multiple service agreement tiers, including KeysightCare Assured, Enhanced, and Application Software Support. See the KeysightCare data sheet for details.
KeysightCare Assured	KeysightCare Assured goes beyond basic warranty with repair services that include committed TAT and unlimited access to technical experts.
KeysightCare Enhanced	KeysightCare Enhanced includes all the benefits of KeysightCare Assured plus Keysight's accurate and reliable calibration services, accelerated, and committed TAT, and technical response.
Keysight Support Portal & Knowledge Center	All KeysightCare tiers include access to the Keysight Support Portal where you can manage support and service resources related to your assets such as service requests, and status, or browse the Knowledge Center.
Education Services	Build confidence and gain new skills to make accurate measurements, with flexible Education Services developed by Keysight experts. Including Start-up Assistance.
Alternative product acquisition	
KeysightAccess	Reduce budget challenges with a subscription service enabling you to get the instruments, software, and technical support you want for your test needs.

Recommended Services

Maximize your test system up-time by securing technical support, repair, and calibration services with committed response and turnaround times. 1-year KeysightCare Assured is included in every new instrument purchase. Obtain multi-year KeysightCare upfront to eliminate the need for lengthy and tedious paperwork and yearly requests for maintenance budget. Plus, you benefit from secured service for 2, 3, or 5 years.

Service	Function
KeysightCare Enhanced*	Includes Tech Support, Warranty and Calibration
R-55B-001-1	KeysightCare Enhanced – Upgrade 1 year
R-55B-001-2	KeysightCare Enhanced – Extend to 2 years
R-55B-001-3	KeysightCare Enhanced – Extend to 3 years (Recommended)
R-55B-001-5	KeysightCare Enhanced – Extend to 5 years (Recommended)
KeysightCare Assured	Includes Tech Support and Warranty
R-55A-001-2	KeysightCare Assured – Extend to 2 years
R-55A-001-3	KeysightCare Assured – Extend to 3 years
R-55A-001-5	KeysightCare Assured – Extend to 5 years
Start-Up Assistance	
PS-S10	Included – instrument fundamentals and operations starter
PS-S20	Optional, technology & measurement science standard learning

* Available in select countries. For details, please view the [datasheet](#). R-55B-001-2/3/5 must be ordered with R-55B-001-1.



Keysight enables innovators to push the boundaries of engineering by quickly solving design, emulation, and test challenges to create the best product experiences. Start your innovation journey at www.keysight.com.

This information is subject to change without notice. © Keysight Technologies, 2014 – 2024, Published in USA, October 18, 2024, 5992-0014EN