

Keysight 85059B

Precision Calibration Kit, 1.0 mm

Data Sheet

The Keysight 85059B is a 1.0 mm calibration/verification kit designed for vector network analyzer systems operating over the frequency range of DC to 120 GHz. The opens, shorts and loads in this kit were optimized to provide accurate calibrations over the specified frequency range.

Electrical Specifications for 1.0 mm 50 ohm Devices

Device	Frequency (GHz)	Parameter	
Data-Based Model		Deviation from Nominal Phase Degrees	
Short 1, 2, 3, & 4 male and female	DC to 20	1.50	
	20 - 50	2.30	
	50 - 80	3.25	
	80 - 100	3.50	
	100 - 120	4.00	
Open male and female	DC to 20	2	
	20 - 50	3	
	50 - 80	7	
	80 - 100	8	
	100 - 120	8	
Data-Based Model		Return Loss (dB)	
Load male and female	DC to 18	30	
	18 - 40	26	
	40 - 50	24	
Device	Frequency (GHz)	Parameter	
Data-Based Model		Return Loss (dB)	Insertion Loss (dB)
Adapters	DC to 110	14	-0.5
	110 - 120	14	-0.7



Replaceable Parts

Description	Qty Per Kit	Keysight Part Number
Calibration Devices (1.0 mm)		
1.3 mm offset short 1 male	1	85059-60027
2.45 mm offset short 2 male	1	85059-60029
3.326 mm offset short 3 male	1	85059-60031
4.039 mm offset short 4 male	1	85059-60033
1.3 mm offset short 1 female	1	85059-60028
2.45 mm offset short 2 female	1	85059-60030
3.326 mm offset short 3 female	1	85059-60032
4.039 mm offset short 4 female	1	85059-60034
Offset open male	1	85059-60053
Offset open female	1	85059-60054
Lowband load male	1	85059-60019
Lowband load female	1	85059-60020
Adapters (1.0 mm)		
Adapter male-male	1	85059-60044
Adapter female-female	1	85059-60045
Adapter male-female	1	85059-60046
Calibration Kit Storage Case		
Box with customized foam inserts	1	1540-2330
Wrenches		
6 mm open-end wrench	1	8710-2156
6 mm, 45 N-cm (4 in-lb) torque wrench	1	8710-2812
14 mm, 45 N-cm (4 in-lb) torque wrench	1	8710-2813
Miscellaneous Items		
Operations and Service Guide	1	85059-90005
10x Magnifying Glass	1	1000-1114
Protective end caps	as required	1401-0202

www.keysight.com/find/85059B