Waveguide Design Workflows for Near-Eye Display Systems

Designing AR Glasses with Optical Simulation


Introduction

Near-eye display systems rely on waveguides and optical combiners to deliver virtual images while maintaining a compact and lightweight form factor. Designing these systems requires engineers to balance image quality, field of view, brightness, eye box performance, optical efficiency, and user comfort.

Virtual Reality (VR) systems generally use conventional imaging optics, such as pancake or Fresnel lenses, without waveguides. This overview focuses on waveguide-based AR near-eye displays.

Waveguide-based display architectures for AR smart glasses introduce unique optical challenges that are not typically encountered in conventional imaging systems.

Engineers must understand light propagation within the waveguide, analyze coupling efficiency, evaluate diffraction behavior, and identify potential sources of stray light before moving to hardware prototypes.



KEYSIGHT

Common Near-Eye Display Design Challenges

Modern near-eye display systems often face challenges such as:

- Optical losses during in-coupling, propagation and/or pupil expansion and out-coupling
- Image non-uniformity across the field of view
- Eye box uniformity requirements and eye relief limitations
- Chromatic artifacts and color non-uniformity
- Stray light and ghost image generation
- Brightness requirements for outdoor visibility
- Tradeoffs between performance, size, and manufacturability

These challenges frequently require multiple design iterations and system-level analysis to fully understand their impact on the user experience.

Using Simulation to Evaluate Waveguide Performance

Simulation enables engineers to evaluate waveguide performance before building hardware. Optical models can be used to study light propagation, diffraction behavior, image quality, and optical efficiency while identifying potential design issues early in development.

Advanced techniques such as k-space analysis provide insight into allowable propagation paths and help engineers understand clipping boundaries, coupling behavior, and sources of stray light within waveguide systems. These methods can be especially valuable when working with geometric or diffractive waveguide architectures.

Supporting the Complete Near-Eye Display Workflow

Successful near-eye display development often requires engineers to move between display design, waveguide analysis, optical simulation, stray light evaluation, and system-level performance assessment. By analyzing these subsystems together, teams can better understand design tradeoffs and make more informed engineering decisions throughout the development process.

Key Takeaways

- Waveguides are a foundational technology for many AR near-eye display systems.
- Design and simulation helps engineers evaluate performance before hardware is built.
- K-space analysis improves understanding of waveguide behavior and stray light.
- System-level workflows support better decisions across display, waveguide, and sensing subsystems.
- Early analysis reduces development risk and accelerates design iterations.

As a mission-critical design enablement partner, Keysight connects design, emulation, and test so customers can solve the world's most complex engineering challenges. Accelerate innovation at www.keysight.com.

KEYSIGHT

This information is subject to change without notice. © Keysight Technologies, 2026, Published in USA, November 3, 2026, 3126-1878.EN