

Keysight InfiniiVision 2000A and 3000A X-Series Oscilloscopes

Oscilloscope Firmware Version 2.67

Release Date:	31 August 2025
Instrument software version:	Revision 2.67
File Names:	2000XSeries.02.67.20250807001.ksx, 3000XSeries.02.67.20250807001.ksx

CAUTION

If your oscilloscope's software version is prior to 2.41, you will need to change the suffix of the upgrade file from .ksx to .cab.

Do not "unpack" or "unzip" the renamed .cab upgrade file; you could potentially only load a portion of the required files in the package, and this could result in your oscilloscope becoming non-operational, requiring it to be sent to a Keysight service center to be repaired.

NOTE

Due to a lack of browser support for Java-based applications, support for the legacy Java-based remote front panel has been removed. A modern HTML5-based remote front panel is available.

Bug Fixes for both 2000A and 3000A

- Modified the firmware to allow users to enter probe attenuation values in smaller increments. No longer restricting the user to set attenuation values to a 1-2-5 value.

Oscilloscope Firmware Version 2.66

Release Date:	1 February 2024
Instrument software version:	Revision 2.66
File Names:	2000XSeries.02.66.20240123001.ksx, 3000XSeries.02.66.20240123001.ksx

CAUTION

If your oscilloscope's software version is prior to 2.41, you will need to change the suffix of the upgrade file from .ksx to .cab.

Do not “unpack” or “unzip” the renamed .cab upgrade file; you could potentially only load a portion of the required files in the package, and this could result in your oscilloscope becoming non-operational, requiring it to be sent to a Keysight service center to be repaired.

NOTE

Due to a lack of browser support for Java-based applications, support for the legacy Java-based remote front panel has been removed. A modern HTML5-based remote front panel is available.

Enhancements for both 2000A and 3000A

- Added a new Trig Out mode – Trigger Source. The raw trigger signal from the oscilloscope's trigger circuit is output to Trig Out when Trigger Source is selected.

Bug Fixes for both 2000A and 3000A

- Fixed issue in which saving a PNG 24-bit image does not work after recalling a setup file.
- Fixed issue where the phase measurement is incorrect after recalling a setup file with different source settings.

Oscilloscope Firmware Version 2.65

Release Date:	31 March 2021
Instrument software version:	Revision 2.65
File Names:	2000XSeries.02.65.20210307001.ksx, 3000XSeries.02.65.20210307001.ksx

CAUTION

If your oscilloscope's software version is prior to 2.41, you will need to change the suffix of the upgrade file from .ksx to .cab.

Do not “unpack” or “unzip” the renamed .cab upgrade file; you could potentially only load a portion of the required files in the package, and this could result in your oscilloscope becoming non-operational, requiring it to be sent to a Keysight service center to be repaired.

NOTE

Due to a lack of browser support for Java-based applications, support for the legacy Java-based remote front panel has been removed. A modern HTML5-based remote front panel is available.

New Features for 3000A

This software revision includes the following new capabilities:

- Added support for the following new perpetual software licenses:
 - o *D3000GENB, D3000AERB, D3000AUTB, D3000PWRB, D3000BDLB*

New Features for 2000A

This software revision includes the following new capabilities:

- Added support for the following new perpetual software licenses:
 - o *D2000GENB, D2000AUTB, D2000BDLB*

Bug Fixes for both 2000A and 3000A

- Corrected wrong number of points returned for the first acquisition after changing acquisition settings.

Oscilloscope Firmware Version 2.60

Release Date:	30 October 2020
Instrument software version:	Revision 2.60
File Names:	2000XSeries.02.60.20201011001.ksx, 3000XSeries.02.60.20201011001.ksx

CAUTION

If your oscilloscope's software version is prior to 2.41, you will need to change the suffix of the upgrade file from .ksx to .cab.

Do not “unpack” or “unzip” the renamed .cab upgrade file; you could potentially only load a portion of the required files in the package, and this could result in your oscilloscope becoming non-operational, requiring it to be sent to a Keysight service center to be repaired.

NOTE

Due to a lack of browser support for Java-based applications, support for the legacy Java-based remote front panel has been removed. A modern HTML5-based remote front panel is available.

Enhancements for 3000A

- New SCPI command to start the probe degauss operation for the N7026A and N2893A probes.

Enhancements for both 2000A and 3000A

- Completed software and built-in online help localization.
- New SCPI commands for clearing persistence data from the display and querying the run state.

Bug Fixes for both 2000A and 3000A

- Fixed network print issue where a valid printer address format was not accepted.

Oscilloscope Firmware Version 2.50

Release Date:	8 March 2019
Instrument software version:	Revision 2.50
File Names:	2000XSeries.02.50.2019022736.ksx, 3000XSeries.02.50.2019022736.ksx

CAUTION

If your oscilloscope's software version is prior to 2.41, you will need to change the suffix of the upgrade file from .ksx to .cab.

Do not “unpack” or “unzip” the renamed .cab upgrade file; you could potentially only load a portion of the required files in the package, and this could result in your oscilloscope becoming non-operational, requiring it to be sent to a Keysight service center to be repaired.

NOTE

Due to a lack of browser support for Java-based applications, support for the legacy Java-based remote front panel has been removed. A modern HTML5-based remote front panel is available.

Enhancements for 3000A

- Added support for the N7026A probe.
- Segmented memory is now a standard feature.

Enhancements for both 2000A and 3000A

- Added support for High-Speed LAN Instrument Protocol (HiSLIP).

Bug Fixes for both 2000A and 3000A

- Fixed an issue of an unrelated error message showing when adjusting the UART/CAN/LIN baud-rate.
- Fixed an issue of the Reference Waveform file (.h5) incorrectly saving data with twice the timebase delay when there is a non-zero delay on the displayed waveform.
- Fixed an issue of the inverted channel mode not displaying the waveform correctly in Averaging Mode.

Changes for both 2000A and 3000A

- Due to a lack of browser support for Java-based applications, support for the legacy Java-based remote front panel has been removed. A modern HTML5-based remote front panel is available.
- As of version 2.50, the VNC server software for the remote front panel functionality is no longer bundled with the scope software by default. Upgrading to 2.50 will not delete the VNC server software from the scope, but new scopes will no longer ship with the VNC server software installed. For scopes without the software installed, the Browser Web Control page will provide a link for installing the software.

Oscilloscope Firmware Version 2.43

Release Date:	5 March 2018
Instrument software version:	Revision 2.43
File Names:	2000XSeries.02.43.2018020635.ksx, 3000XSeries.02.43.2018020635.ksx

CAUTION

If your oscilloscope's software version is prior to 2.41, you will need to change the suffix of the upgrade file from .ksx to .cab.

Do not “unpack” or “unzip” the renamed .cab upgrade file; you could potentially only load a portion of the required files in the package, and this could result in your oscilloscope becoming non-operational, requiring it to be sent to a Keysight service center to be repaired.

New Features for the 2000A

This software revision includes the following new capabilities:

- Added support for DSOX2PLUS. See product page on www.keysight.com for details.

Enhancements for the 3000A

- Support for the N7026A probe was added.
- The ability to calibrate the offset was added for the N2820/1A probe.

Enhancements for the 2000A

- The following measurements have been added to the 2000A:
 - o “X@Max”
 - o “X@Min”
 - o “Positive Pulse Count”
 - o “Negative Pulse Count”
 - o “Rising Edge Count”
 - o “Falling Edge Count”

Bug Fixes for both 2000A and 3000A

- An issue preventing a full waveform export in Roll-mode has been corrected.

- An issue preventing DVM's Auto Range from operating correctly in certain acquisition modes has been corrected.

Oscilloscope Firmware Version 2.42

Release Date:	29 March 2017
Instrument software version:	Revision 2.42
File Names:	2000XSeries.02.42.2017032900.ksx, 3000XSeries.02.42.2017032900.ksx

CAUTION

If your oscilloscope's software version is prior to 2.41, you will need to change the suffix of the upgrade file from .ksx to .cab.

Do not “unpack” or “unzip” the renamed .cab upgrade file; you could potentially only load a portion of the required files in the package, and this could result in your oscilloscope becoming non-operational, requiring it to be sent to a Keysight service center to be repaired.

Enhancements for both 2000A and 3000A

- Both the DVM and training signal features are now included as standard.
- Probe attenuation can now be set down to 0.001

Enhancements for the 3000A

- Remote User Interface support was added for the N2820A probe.

Bug Fixes for both 2000A and 3000A

- An issue with certain timebase changes affecting waveforms displayed in high resolution or averaging mode has been corrected.
- An issue with Single acquisitions in averaging mode has been corrected.
- Certain conditions are now better propagated through the AER and TER registers.
- The timebase delay control limit is now better calculated.
- Improvements were made to the FFT algorithm for certain conditions.
- An issue with the channel invert function and setup files was corrected.
- An issue with the Delay measurement sometimes not measuring from the edge closest to the trigger reference point has been corrected.
- An issue with the calculation of the length header for ASCII formatted binary blocks has been corrected.

- An issue with clearing the trigger event register (TER) with *CLS has been corrected.
- An issue with saving an FFT .csv file has been corrected.
- The VTIme measurement now works properly on digital channels.

Bug Fixes for the 3000A

- Certain N7020A probe calibration failures are now more accurately detected.

Bug Fixes for the 2000A

- The Trig 50% feature now works properly on 2 channel scopes.

Oscilloscope Firmware Version 2.41

Release Date:	2 November 2015
Instrument software version:	Revision 2.41
File Names:	2000XSeries.02.41.2015102200.cab, 3000XSeries.02.41.2015102200.cab

CAUTION

Do not “unpack” or “unzip” the .cab upgrade file; you could potentially only load a portion of the required files in the package, and this could result in your oscilloscope becoming non-operational, requiring it to be sent to a Keysight service center to be repaired.

Enhancements for both 2000A and 3000A

- Updates to some German translations in the Help text were made.

Bug Fixes for both 2000A and 3000A

- A Device Clear sent over the USB interface will now work more reliably.
- Powering on the oscilloscope with a PC connected via USB has been made more reliable.
- The calculation of a LIN checksum has been improved.
- A typo in the remote user interface for the negative duty cycle measurement has been corrected.

Oscilloscope Firmware Version 2.40

Release Date:	September 8, 2015
Instrument software version:	Revision 2.40
File Names:	2000XSeries.02.40.20150828001.cab, 3000XSeries.02.40.20150828001.cab

CAUTION

Do not “unpack” or “unzip” the .cab upgrade file; you could potentially only load a portion of the required files in the package, and this could result in your oscilloscope becoming non-operational, requiring it to be sent to a Keysight service center to be repaired.

New Features for 2000A and 3000A

This software revision include the following new capabilities:

- Negative Duty Cycle has been added.

Enhancements for both 2000A and 3000A

- mDNS setting now persists through power cycle.
- Improved latency when using SCPI Socket or SPCI Telnet interfaces on networks without NETBIOS

Enhancements for 3000A

- Ax+B math operator now allows for negative values of A.

Bug Fixes for both 2000A and 3000A

- Improved stability of Tablet Remote Front Panel.
- DVM now handle channel invert use case more appropriately.

Oscilloscope Firmware Version 2.39

Release Date:	10 March 2015
Instrument software version:	Revision 2.39
File Names:	2000XSeries.02.39.20151022602.cab, 3000XSeries.02.39.20151022602.cab

CAUTION

Do not “unpack” or “unzip” the .cab upgrade file; you could potentially only load a portion of the required files in the package, and this could result in your oscilloscope becoming non-operational, requiring it to be sent to a Keysight service center to be repaired.

New Features for 2000A and 3000A

This software revision include the following new capabilities

N/A

Enhancements

- Bit rate measurement units have been improved.
- Reference memory skew behavior is improved in some situations.

Bug Fixes

N/A

Oscilloscope Firmware Version 2.38

Release Date:	11 Nov 2014
Instrument software version:	Revision 2.38
File Names:	2000XSeries.02.38.2014110300.cab, 3000XSeries.02.38.2014110300.cab

CAUTION

Do not “unpack” or “unzip” the .cab upgrade file; you could potentially only load a portion of the required files in the package, and this could result in your oscilloscope becoming non-operational, requiring it to be sent to a Keysight service center to be repaired.

New Features for 2000A and 3000A

This software revision include the following new capabilities

- Software is now Keysight Technologies branded.
- **Trigger Rate SCPI query has been added - TRIGger:FREQuency? <gate time in sec>**
- New bit rate measurement has been added.

New Features for 3000A

This software revision include the following new capabilities

- N2804A/N2805A 100MHz/300MHz differential probe support has been added.
- N7020A Power Rail probe support has been added.

Enhancements

Bug Fixes

- AER/TER behavior is improved.
- *STB behavior is improved

Oscilloscope Firmware Version 02.37.2014052002**Release Date: May 21, 2014****File Names:****2000XSeries.02.37.2014052002.cab****3000XSeries.02.37. 2014052002.cab****Enhancements**

For both the 2000X and 3000X families:

- Java application security enhancement to track Java engine security improvements
- Waveform Generator accuracy is now improved in a number of situations.
- V average measurement resolution is much improved for small measurements

For the 3000X family:

- N2820A/ N2821A high sensitivity current probes – Range for the user defined resistance has been expanded to now include 10 microOhms to 1 MegaOhms
- Power application improvements
 - Switching loss measurement now behave better around 0 amps
 - Inrush current measurement is now more reliable
 - Efficiency measurement
 - Scaling of waveforms is now optimized, less clipping in some situations
 - Added DC to DC, DC to AC, AC, to AC efficiency measurement.
 - Absolute current is used to give correct result, even if probe is hooked up backwards
 - Current Harmonic measurement
 - Now uses BH window as default, just like the U1881A
 - Transient response – triggering is made more flexible

Defects Addressed

- :MEAS:DEF THR, PERCent,95,10,5 no longer given an out of range error
- Current Harmonic measurement now correct scales grid at decibels to Vrms setting's change.

Oscilloscope Firmware Version 02.36.2013091300**Release Date: Sept 21, 2013****File Names:****2000XSeries.02. 36.2013091300.cab****3000XSeries.02. 36.2013091300.cab**

To upgrade your oscilloscope, download the appropriate .cab file, and load this complete file into the oscilloscope.

CAUTION

Do not “unpack” or “unzip” the .cab upgrade file; you could potentially only load a portion of the required files in the package, and this could result in your oscilloscope becoming non-operational, requiring it to be sent to a Keysight service center to be repaired.

This version of the oscilloscope firmware includes the items below:

Enhancements

For both the 2000X and 3000X families:

More flexible FPGA programming for the LAN/VGA module.

Oscilloscope Firmware Version 02.35.2013061800**Release Date: June 24, 2013****File Names:****2000XSeries.02.35.2013061800.cab****3000XSeries.02.35.2013061800.cab**

To upgrade your oscilloscope, download the appropriate .cab file, and load this complete file into the oscilloscope.

CAUTION

Do not “unpack” or “unzip” the .cab upgrade file; you could potentially only load a portion of the required files in the package, and this could result in your oscilloscope becoming non-operational, requiring it to be sent to a Keysight service center to be repaired.

This version of the oscilloscope firmware includes the items below:

Enhancements

For both the 2000X and 3000X families:

Default cursors placement will no longer overlay cursors on the same value.

For the 3000X family:

N2820A high sensitivity 2 channel current probe support has been expanded to allow for a greater range of user defined resistance.

LIN error triggering has been added.

WaveGen modulation frequency now has more granularity for user adjustment.

Defects Addressed

For the 2000X and 3000X family:

Mask “save on Error” capability now works for SINGLE acquisitions

Scope will behave better in higher activity LAN networks

A number of bitmaps behaviors have been improved for some tablets

For the 3000X family:

LIN 2.0 decoding now better handles the Checksum field.

An Arb file import error has been addressed; it no longer skips some time column data.

For I2C decoder search: previously, read packets sometimes erroneously found during write searches.

Oscilloscope Firmware Version 02.31.2013040901**Release Date: April 12, 2013****File Names:****2000XSeries. 02.31.2013040901.cab****3000XSeries. 02.31.2013040901.cab**

To upgrade your oscilloscope, download the appropriate .cab file, and load this complete file into the oscilloscope. **Do not “unzip” the file.**

This version of the oscilloscope firmware includes the items below:

Defects Addressed

For the 2000X and 3000X family:

SW upgrade process has been improved to more consistently allow auto reboot without cycling power on the oscilloscope. In previous software revisions, some small set of USB thumb drives used to upgrade the system software prevented the automatic rebooting when the transfer process finished, requiring the users to remove the thumb drive and cycle power.

Oscilloscope Firmware Version 02.30.20130405**Release Date: April 5, 2013****File Names:****2000XSeries. 02.30.2013040502.cab****3000XSeries. 02.30.2013040502.cab**

To upgrade your oscilloscope, download the appropriate .cab file, and load this complete file into the oscilloscope. Do not “unzip” the file.

This version of the oscilloscope firmware includes the items below:

Enhancements

For both the 2000X and 3000X families:

A multichannel HDF5 file format has been added for export, allowing direct waveform data input into Agilent's InfiniiView N8900A offline viewer application.

The duty cycle measurement resolution is improved beyond 0.1%, if measurement data can support more.

When stopped, roll mode waveforms now expand about the trigger reference point, instead of just the right side of the display.

Added :TRIGger:LEVel:AUTosetup – This will set the trigger level to the 50% voltage for all displayed analog channels.

For the 2000X family:

SW option DSOX2MEMUP has been added to allow all channels up to 1 Megabyte of MegaZoom acquisition memory.

The standard memory has been upgraded to 100 Kilobytes of MegaZoom acquisition memory per channel.

SW option DSOX2EMBD has been added to support hardware accelerated I²C and SPI serial triggering and analysis, including decode, lister, and search capabilities.

SW option DSOX2AUTO has been added to support hardware accelerated CAN and LIN serial triggering and analysis, including decode, lister, and search capabilities.

SW option DSOX2COMP has been added to support hardware accelerated RS232/UART serial triggering and analysis, including decode, lister, and search capabilities.

For the 3000X family:

N2820A high sensitivity 2 channel current probe support has been added. This allows current measurements down to micro amp range while simultaneously viewing the large signal behavior on the second channel of the probe.

When the WaveGen powers down in arbitrary waveform mode, the arbitrary waveform will persist through the power cycle.

The ability to reset the measurement statistics from the Quick Action key has been added.

Defects Addressed

For the 2000X and 3000X family:

Scope labels on the tablet interface now display the correct scope information.

Overshoot measurement now more consistently chooses the edge closest to the trigger reference.

Scope no longer erroneously indicates that it will not work with Java 7 (it does work)

AutoIP is disabled before user network settings are applied during power-up. It was enabled on previous releases. DHCP has always been disabled before network settings were applied.

For the 3000X family:

The N2750A family will operate properly when the button is pressed during a probe calibration operation.

Oscilloscope Firmware Version 02.20.2012110802**Release Date: Nov 12, 2012****File Names:****2000XSeries. 02.20.2012110802.cab****3000XSeries. 02.20.2012110802.cab**

To upgrade your oscilloscope, download the appropriate .cab file, and load this complete file into the oscilloscope. Do not “unzip” the file.

This version of the oscilloscope firmware includes the items below:

Enhancements

For both the 2000 and 3000 families:

A tablet compatible version of the Remote Front Panel operation is now available from the Oscilloscopes Web page, This includes iPad™ and many Android based tablets.
Modulation capability has been added to the WaveGen option. This include AM, FM, FSK
Measurements are now allowed when in XY mode, except for “X at Min Y” and “X at Max Y”.
The user probe ratio setting of 2000, 5000, and 10000 have been added.
The resolution of the Phase measurement is improved if in Averaging or High Resolution acquisition modes.
Added WMemory<N> as a valid source for the BLANK, VIEW, and STATUS commands.

For the 3000X family:

The N2750A family of InfiniiMode probes support has been added. These provide three different types of probe tip accessories standard – browser, solder-in and socketed. Both solder-in and socketed tip with the probe provide three measurement modes – differential, single-ended and common mode.
UART baud rate support for 10 Mbaud has been added.
For ARINC 429 serial trigger and decode User defined Baud Rate support has been added.
When adjusting the frequency of Arbitrary waveforms, the resulting waveform output is now more continuous.
Power App improvements
Measurements are now grouped by category for ease of use (Input, Switching & Output).
For Auto De-skew, BW Limit is turned on to help reduce false triggering on noise.
After executing an Auto Setup, on successful operation, the application now returned to the previous menu.
Added new power loss\cycle measurement for switching loss.
Slew rate analysis now uses differentiate math function for better results.
Now allows negative output level for turn on, turn off and transient response test setting.
PSRR horizontal grid now labels for both ends of grid if it doesn't overlap.

Defects Addressed

For the 2000X and 3000X family:

The SCPI status byte register will now update immediately whenever a new telnet or socket connection is made.

Saving of XY data is now improved, it was saving only half of the data previously.

The *TST? Now returns 0|1, to represent failing and passing, instead of -0|+0.

When doing a Single, TRG bit (bit0 in the Status Byte Register) is now updated appropriately.

For the 3000X family:

Users can now load Arb Waveform .csv files with 3, 4, and 5 columns.

Autoscale now more reliably scales on signals with lowest frequency in the range from 25 Hz to 50Hz.

Waveform data save to thumbdrive - digital channel data is now correct at end of waveform data record range.

I2C trigger/decode now handles slow edges as correctly.

The Math trend function will now better track the end of the waveform.

Power

Switching loss math waveform conduction calculation for Rds or Vce(sat) now plots correctly in zoom mode.

When using Rds or Vce(sat), and moving math vertical offset beyond screen, values now clips.

Crest factor now calculates from modulus of negative or positive peak as opposed to only positive peaks.

Power App demo for current harmonics, setting for frequency is now 50Hz, previously 60Hz.

Stats are now reset when changing measurement type for Modulation power measurement.

Oscilloscope Firmware Version 02.11.2012040400**Release Date: April 11, 2012****File Names:****2000XSeries.02.11.2012040400.cab****3000XSeries.02.11.2012040400.cab**

To upgrade your oscilloscope, download the appropriate .cab file, and load this complete file into the oscilloscope. Do not “unzip” the file.

This version of the oscilloscope firmware includes the items below:

Enhancements

For both the 2000 and 3000 families:

DSOXASV option has been added

This allows the oscilloscope to be used with the 64997A, Agilent Spectrum Visualizer software.

The 64997A software runs on a PC and uses data acquired by the oscilloscope to provide frequency domain views.

For the 3000X family:

CAN eye-diagram mask testing has been added to the DSOX3AUTO, Automotive Serial Triggering and Analysis option. The eye-diagram testing also requires the DSOX3MASK option.

Defects Addressed

For the 3000X family:

The CAN serial Lister, which is part of the DSOX3AUTO option, now will display eight bytes of data in the Data column, where previously only seven bytes would be displayed.

Oscilloscope Firmware Version 02.10.2012022200**Release Date: Feb 28, 2012****File Names:****2000XSeries.02.10.2012022200.cab****3000XSeries.02.10.2012022200.cab**

To upgrade your oscilloscope, download the appropriate .cab file, and load this complete file into the oscilloscope. Do not “unzip” the file.

This version of the oscilloscope firmware includes the items below:

Enhancements

For both the 2000 and 3000 families:

DSOXDVM option has been added

This allows DVM measurements directly from your standard oscilloscope probe, or any probe.

Readout is displayed in a large, easy to read DMM format. It runs continuously, independent of the oscilloscope waveform acquisitions and triggering system.

Improved Network Printer support has been added. Supported protocols now include LPD, IPP, and HP JetDirect™ print protocols.

USB Keyboard support has been added for filenames, labels, and similar string entry fields.

Annotation capability has been added. This is accessible via the UTILITY menu, and can also use the new USB Keyboard as an input method.

The waveform Math Divide operator is now standard on all oscilloscopes.

For the 3000X family:

The measurement statistics are no longer reset at Main to Zoom timebase window changes.

Defects Addressed

For both the 2000 and 3000 families:

FFT amplitude accuracy has been improved when using Vrms scaling.

Oscilloscope Firmware Version 02.01.2011111500**Release Date: Nov 15, 2011****File Names:****2000XSeries.02. 01.2011111500.cab****3000XSeries.02. 01.2011111500.cab**

To upgrade your oscilloscope, download the appropriate .cab file, and load this complete file into the oscilloscope. Do not “unzip” the file.

This version of the oscilloscope firmware includes the items below:

Enhancements

For both the 2000 and 3000 families:

Added a remote command to turn the menu off line

:SYSTem:MENU OFF

For network printing, the allowed character set has been expanded to a number of non – alphanumeric characters.

Defects Addressed

For both the 2000 and 3000 families:

Russian help is now fully updated for new SW Rev 2.00 capabilities

Oscilloscope Firmware Version 02.00.2011101301**Release Date: Oct 17, 2011****File Names:****2000XSeries.02.00. 2011101301.cab****3000XSeries.02.00. 2011101301.cab**

To upgrade your oscilloscope, download the appropriate .cab file, and load this complete file into the oscilloscope. Do not “unzip” the file.

This version of the oscilloscope firmware includes the items below:

Enhancements

For both the 2000 and 3000 families:

For web server ‘Get Image’ functionality, users can now specify whether a white background or a black background is desired, via a new Invert Graticule check box on the web page.

Waveform generator frequency accuracy boosted for frequencies below 6kHz.

In Segmented acquisition mode, memory depth is now better matched to screen width for vernier timebase setting. This allows for reduced holdoff time between segments when at vernier settings.

- **:MARKer:X1Position? and :MARKer:X2Position? now will return the sign (instead of absolute value) when the unit is Hz. Users will be able to know the real location of the marker.**

Entry knob assignment now more consistently remembers the softkey it was assigned when switching back into a menu.

For the 3000 family:

Arbitrary Waveform Generator capability has been added to the DSOX3WAVEGEN option. This now allows users to create waveforms directly from the scope channel data, edit them, and save and recall arbitrary waveform data.

DSOX3VID application is now available. This application allows advanced Video triggering.

DSOX3AERO application is now available. This application allows serial triggering and decode for Mil-Std 1553 and ARINC 429 standards.

DSOX3FLEX application is now available. This application allows serial triggering and decode for FlexRay™ standard

DSOX ADVMATH application is now available. This application expands the Waveform Math capability significantly by adding the following operators

Divide

Base 10 logarithm

Natural logarithm

Exponential

Base 10 Exponential

Absolute value

Linear equation - $A \cdot x + B$

Magnify

Low Pass filtering

High Pass filtering
Measurement Trend
Chart mode for timing channels
Chart mode for timing channels with a state clock
DSOXPWR application is now available This application allows for Power measurements to be done in the DSO-X 3000 series oscilloscopes, including
Harmonics
Inrush current
Switching loss
Modulation
Power Quality
Turn Off, Turn On
Transient Response
Output Ripple
Power Supply Rejection Ratio
Slew Rate
This option also enables U1881-003, Agilent's PC based Power Measurement Application which also includes advanced report generation and SOA measurement capability.
RS232 user defined baud rate extended down to 100 b/s.
Serial Lister will now issue a warning if its capacity is reached.
113xA Probe offset calibration is now more accurate.
:MEASure:STATistics:DISPlay {{ON | 1} | {OFF | 0}} has been added to allow remote control and query of the measurement statistics display state.

Defects Addressed

For both the 2000 and 3000 families:

Auto triggering now starts up more reliably from the stopped state.
When the X1 and X2 cursors are slaved together, the delta time between them is now constant as they move through the zoom window, and no longer changes at the zoom window boundary.
The probe attenuation factor no longer increments after power cycles, in certain situations.
Fixed logic cursor binary and hex values reporting 'don't care' when outside the zoom window.
Reference memory is now plotted at correct skew in zoom window at non-zero delay settings.
Certain instances where the first trigger event may have been missed have been corrected.
An error message is no longer displayed when loading a mask while the trigger source is set to WaveGen.
The Auto Mask feature will now cancel a previous request if it is still in progress when either the timebase scale or the delay are changed.

For the 3000 family:

UART decode and trigger sampling at certain low baud rates have been corrected.
Edge search indicators now indicate the correct position for roll mode waveforms.
Search now works on waveforms acquired in High Resolution mode when stopped.
Certain instances where a CAN serial trigger configured for standard length IDs would trigger on an extended ID have been corrected.
Cursor placement on zoomed square root waveforms is improved in consistency and accuracy.

Oscilloscope Firmware Version 01.20.2011063000**Release Date: June 30, 2011****File Names:****2000XSeries.01.20.2011063000.cab,
3000XSeries.01.20.2011063000.cab**

This version of the oscilloscope firmware includes the items below:

Enhancements

For both the 2000 and 3000 families:

1 mV/div sensitivity is now supported on all analog channels.

The web interface now supports an additional type of remote front panel that mimics the physical front panel as well as the scope GUI with live waveforms.

A QR code has been included in the oscilloscope GUI – find it and check it out.

Cursor functionality has been extended to allow for manual phase and ratio measurements.

:MEASure:CLEAr remote command now clears the :MEASure:ALL snapshot data from the screen.

Saving invalid MATH data to Reference Memories is now prevented.

:TRIGger:FORCe" command has been added.

:DIGitize performance has been improved.

For the 3000 family:

Waveform Generator now supports the following additional shapes: Sinc, Exponential Rise, Exponential Fall, Cardiac, and Gaussian Pulse.

Measurement statistics now allow user selectable finite windowing (up to 2000 measurements) over which to calculate the statistics.

For measurement statistics, relative standard deviation may be chosen as an alternative to the previous standard deviation result.

For the integrate Math function, a DC offset adjustment is now included to zero out small DC components.

For the FFT Math function, the FFT can now be plotted in Vrms as well as dB.

OR triggering has been added. All channels, both analog and digital, can be included in the specification.

Edge then Edge triggering has been added – This allows the scope to arm on a specified edge on any channel, then delay by time, and then trigger on the Nth edge on a specified channel.

For the N2744A probe adapter, the P671X and P670X series of optical to electrical converters are now supported.

Defects Addressed

USB termination character issue is resolved allowing program to selectively use this capability when communicating with oscilloscope.

ASCII XY file data for digital channels is improved when saving analog and digital channels. It now gives valid data for data after the trigger point.

:WAVEform:DATa header information is corrected for the amount of ASCII data bytes transmitted. It formerly assumed one too few bytes per data point.

Horizontal plot placement of under sampled digital channels is improved and much more consistent across delay and time/div settings.

When only logic channels are on, the full memory can now be used.

The Nth Edge Burst trigger mode's Edge control now works correctly for values > 32767 .



Oscilloscope Firmware Version 01.10.2011042700

Release Date: April 27, 2011

File Names:

2000XSeries.01.10.2011042700.cab,

3000XSeries.01.10.2011042700.cab

Defects Addressed

Corrected LXI XML identification document

Oscilloscope Firmware Version 01.10.2011031600**Release Date: Mar 16, 2011****File Names:****2000XSeries.01.10.2011031600.cab,
3000XSeries.01.10.2011031600.cab**

This version of the oscilloscope firmware includes the items below:

Enhancements

Waveform Math functions with two operands (+, *, -) are now enabled between Ch1 and Ch3 or 4, and also between Ch2 and Ch3 or Ch4.

For I2S triggering specification, binary trigger patterns may now include 'don't care' states for individual bits in the trigger pattern specification.

Waveform intensity is much better matched and balanced across a range of operating conditions. Measurement threshold range has increased to 0% - 100% from 5% - 95%

Web interface page for launching the Remote Front Panel functionality has improved graphics.

Waveform update rate is improved at 1 ms/div.

Display of waveforms while stopped is improved for pan & zoom when acquired in high resolution mode.

Improved user interface responsiveness when changing Lister search criteria for deep records.

Delay readout is now displayed when adjusting delay while in Roll mode.

Recall setup via the web interface now signals user if an issue is detected during recall.

Loading of data files (.msk, .h5) is improved for Chrome™ browser.

Installation of application SW licenses via the web now prompts the user to reboot with a "please cycle power" message.

For the N2744A probe adapter, the P5205 and P5210 high-voltage differential probes are now supported.

User defined screen saver text entry now handles spaces.

Measurement statistics are now reset when turning on the Mask Measure on Error feature.

Automatic labels assigned to serial sources now indicate which serial bus the source is associated with.

CAN baud rate now supports up to 5 Mbits/s

LXI improvements for compliance

Defects Addressed

Instrument more robustly handles mask file import from mask files created for Infiniium oscilloscopes.

Temporary delay readout is now erased correctly.

Scope now displays an advisory during Autoscale if the instrument is un-calibrated.

Display blinks less during power up sequence.

When using the N2744A probe adapter, offset is now defaulted to 0.0V for probes without offset control.

Fixed offset error in waveform data saved in high resolution mode.

Calibration time (hours field) now no longer changes on subsequent presses of 'Cal Status' key in Utility-> Service menu.

Progress bar now shows several more steps when saving CSV and ASCII waveforms.

Zoom mode graticule tick marks are better positioned.

When attempting to save an 8-bit BMP file from the web browser (Internet Explorer™) the instrument will now save the data.

The acquisition is no longer reset at save menu format changes.

Web saving of lister data is now more robust when lister is not on.

Improved automatic scaling of vertical settings for the square root math function.

When using cursors, Math units will not stick at 'Hz' after you change operator from FFT.

Oscilloscope Firmware Version 01.01.2010010700

Release Date: Jan. 10, 2011

File Names: 2000XSeries.01.00.0001.cab, 3000XSeries.01.00.0001.cab

This version of the oscilloscope firmware includes the items below:

Enhancements

Self test is improved for more efficient manufacturing of product.

Oscilloscope Firmware Version 1.01.0000

Released Date:	September 2012
Requirements category (e.g., instrument software version):	Revision 01.01.00000
File Name:	2000XSeries.01.00.0000.cab, 3000XSeries.01.00.0000.cab

Initial Release

© Keysight Technologies 2000-2025