

Keysight InfiniiVision 3000T X-Series Oscilloscopes

Version 7.20.20171026

Released Date:	26 October 2017
Instrument software version:	Revision 7.20.20171026
File Name:	3000XSeriesT.7.20.2017102614.ksx

New Features

This software revision includes the following new capabilities:

- Added USB-PD (Power Delivery) triggering and decode option (DSOXT3UPD).

Enhancements

This software revision includes the following new enhancements:

- Added a SPI decode control for MISO bit delay.
- Added SENT SPC support.
- Minimum Manchester baud rate was decreased to 500bps.
- Added remote commands for gain margin and phase margin.
- Added a FRA option to display either gain or phase separately.
- Added :DISPlay:MESSAge:CLEAr command to dismiss "File Saved Successfully" message.
- Added remote command for setting FRA single-mode frequency
- FRA now allows up to 100 points-per-decade.

- Random trigger holdoff is now allowed in additional trigger modes.
- Added support to load reference waveforms programmatically.
- Added support for the N7026A probe.

Bug Fixes

This software revision includes the following Bug fixes:

- An issue with handling CAN DBC signed integers has been corrected.
- Two channel measurements made with the N2820A probe are now functioning correctly.

Version 7.11.20170612

Released Date:	12 June 2017
Instrument software version:	Revision 7.11.20170612
File Name:	3000XSeriesT.7.11.2017061225.ksx

Bug Fixes

This software revision includes the following Bug fixes:

- Digital channel skew has been corrected.
- Horizontal scale indicators at the bottom of the graticule now update appropriately regardless of the chosen time reference.
- An issue with calibrating an N275XA probe has been corrected.
- An issue with the MEAS:RES query ignoring the count parameter has been corrected.

Version 7.10.20170429

Released Date:	29 April 2017
Instrument software version:	Revision 7.10.20170429
File Name:	3000XSeriesT.7.10.2017042905.ksx

Bug Fixes

This software revision includes the following Bug fixes:

- Fixed an issue where the user's selected language was not remembered after the power was cycled.
- Fixed an issue where an attached mouse would not operate correctly after the power was cycled.

Version 7.10.20170411

Released Date:	11 April 2017
Instrument software version:	Revision 7.10
File Name:	3000XSeriesT.7.10.2017041130.ksx

New Features

This software revision includes the following new capabilities:

- Added Frequency Response Analyzer option (DSOXT3FRA).
- Added Manchester/NRZ serial decode option (DSOXT3NRZ).

Enhancements

This software revision includes the following new enhancements:

- The measurement system has been updated to provide more flexibility to support new measurements with more complex configurations. Some installed measurements will not be recallable if the setup (.scp) file was created with firmware prior to version 7.10.
- Users can now pick specific edges to be used by the Delay measurement.
- Bartlett is now supported as an FFT window choice.
- The UART serial decode now supports baud rates to 12Mbits/s.
- DVM and training signals are now standard features.
- Added random trigger holdoff feature.
- Added support to the NFC option for NFC-F reverse polarity triggering.
- Added Channel Power, Occupied Bandwidth, Adjacent Power Ratio, and Total Harmonic Distortion measurements.

Bug Fixes

This software revision includes the following Bug fixes:

- Fixed an issue where in certain circumstances the Serial Lister would not properly display some UART data.
- Fixed an issue where in certain circumstances the Peak-Peak measurement was incorrect.

Version 4.08

Released Date:	27 July 2016
Instrument software version:	Revision 4.08
File Name:	3000XSeriesT.04.08.2016071801.ksx

New Features

This software revision includes the following new capabilities:

- Added CXPI triggering and decode option (DSOXT3CXPI).
- Added NFC triggering option (DSOXT3NFC).
- Added frequency response analysis to Power Application (PSRR and Control Loop Response).
- Added FFT phase math operator.

Enhancements

This software revision includes the following new enhancements:

- Allow all time domain math functions to be loaded into waveform memories.
- Allow waveform memories to be used as sources for math functions.
- Added user-customizable labels for internal setup files.
- Added GUI indicator for channel invert setting.
- Added SCPI grammar for N2820 zoom and R-sense.
- Added option for a custom time reference location.
- Added “no length control” option to LIN 1.3.
- Improved WaveGen duty cycle granularity.
- Extended WaveGen pulse width limits to 1ns at frequencies $\geq 25\text{kHz}$.
- Extended probe attenuation ratio limits to 0.001 : 1 (-60dB).
- Power Application – Inrush Current - Added support for DC-input power supplies.
- Power Application – Turn-on/Turn-off - Added support for DC-input power supplies.

- Power Application – Turn-on/Turn-off - Added option to specify measurement threshold levels.
- Power Application – Current Harmonics – Added option to automatically determine line frequency.

Bug Fixes

This software revision includes the following Bug fixes:

- Fixed incorrect DVM values in rare circumstances after toggling channel states.
- Fixed error messages when loading CAN FD .dbc files with data fields longer than 8 bytes.
- Fixed crash when saving H5 files with long path strings.
- Improved I²C decode reliability when SCL is acquired on a digital channel.

Version 4.07

Released Date:	20 April 2016
Instrument software version:	Revision 4.07
File Name:	3000XSeriesT.04.07.2016040803.ksx

New Features

This software revision includes the following new capabilities:

- Added remote interface command logger.

Enhancements

This software revision includes the following new enhancements:

- DVM now defaults to DC.
- Cursor state may now be set independently for each cursor.

Bug Fixes

This software revision includes the following Bug fixes:

- Improved USB device mode stability when booting.
- Fixed various LIN symbol file (LDF) parsing errors.
- Fixed 50 Ω probe calibration issue with the Power Analysis application.
- Improved performance when entering the IO menu.
- Fixed FFT vertical units when using a 50 Ω current probe.

Version 4.06

Released Date:	26 May 2015
Instrument software version:	Revision 4.06
File Name:	3000XSeriesT.04.05.2015051200.ksx

New Features

This software revision includes the following new capabilities:

- CAN-FD ISO support has been added to DSOXT3AUTO option.
- Control loop capability in the DSOX3POWER option now includes phase view.

Enhancements

This software revision includes the following new enhancements:

- Up to 10 annotations are now supported.
- mDNS On/Off state is now preserved through power cycles.
- Network connection latencies via Telnet or Socket SCPI ports are improved in some situations in networks without NetBIOS.

Bug Fixes

This software revision includes the following Bug fixes:

- LXI identifier now reports Keysight Technologies.
- DVM has been improved when source channel is inverted.

Version 4.05

Released Date:	16 February 2015
Instrument software version:	Revision 4.05
File Name:	3000XSeriesT.04.05.2015021000.ksx

New Features

This software revision includes the following new capabilities:

- CAN-FD eye testing support has been added to DSOXT3AUTO option.
- LIN Symbolic decoding support has been added to DSOXT3AUTO option.
- Control Loop measurements have been added to the DSOX3POWER option.
- Bitrate measurement has been added.
- Single shot capability has been added to the Waveform Generator.
- DSOX3POWER option now includes Class D harmonics measurements, including mA/W.
- USB frame triggers have been added - Start of Packet, End of Packet, Reset Complete, Enter Suspend, and Exit Suspend.

Enhancements

- DSOX3POWER option now supports Keysight's N7020A Power rail probe.
- N7020A Power rail probe has a number of behavior improvements; improved autoscale; added calibration detection; improved trigger level interaction; expansion is now center screen.
- DISPlay:BACKLIGHT [ON|OFF] command has been added.

Bug Fixes

- A number of missing localized help screen strings and GUI strings have been added.
- "FFT" is now a valid waveform source for a number of SCPI commands.
- Status byte behaviors are improved.

Version 4.00

Released Date:	October 2014
Instrument software version:	Revision 04.00.00000
File Name:	3000XSeriesT.04.00.2014101304.cab

Initial Release

© Keysight Technologies 2000-2017